

# Water Power

Large scale hydroelectric power has been used worldwide for a long time to generate huge amounts of power from water stored behind massive dams. Small scale hydropower has been used for hundreds of years for manufacturing, including milling grain, sawing logs and manufacturing cloth. However, it can also be used **without a dam** to generate electricity for home scale remote power systems. These so-called micro-hydro installations can be a very good complement to a solar power system, as they produce electricity 24 hours a day.

**Waterwheels**--It's important to differentiate between water wheels and water turbines. A water wheel is the antique version we are all familiar with--a massive wooden wheel that slowly turns as the creek pours down over it. Water wheels spin slowly, but with lots of torque. This presents problems for generating electricity, as complex gearing is required to reach a rotation



speed high enough to produce power with an alternator or generator. By the time this torque is sent through the gears, a huge amount of power has been lost to friction. However, one of our neighbors did construct a water wheel generator that produces a steady 2 amps of power, 24 hours a day. He used a natural dam (a log that fell across the creek years ago) to get the fall and to mount the generator on. Some of the locals were positive it wouldn't work, but that was 6 years ago, and the device is still producing power now! [Click here for more information on this clever water wheel.](#)

**Turbines**--All of the commercial micro hydro generators available today use a small turbine connected

to an electrical generator or alternator. Water is collected in an intake pipe upstream, travels down to the turbine in plastic pipe, and is forced through one or more nozzles by its own gravity pressure. No dam is needed; systems without a dam are called "run of river" systems. By this time, the water is moving VERY fast, and it spins the turbine wheel very fast. Power is generated by a generator or alternator directly connected to the turbine wheel (no gears or pulleys needed). All of the factors below must be calculated correctly for your micro-hydro equipment to make power most efficiently. All commercial micro-hydro setups are custom-made by the manufacturer for your specific application. For proper operation, you must supply the manufacturer with specific data about your site, most importantly the vertical drop in feet (called "head"), the amount of water flow available during different seasons in gallons per minute, and the length of pipeline required to get a sufficient head.

Look for more information on home built water turbines here soon!

- In general, for a water turbine you need at least 3 feet of fall and at least 20 gallons per minute of flow. If you have more fall (head), less water is required. You can calculate potential head with a water level, a contractor's level and stadia rod, or with just a string level attached to a measuring stick. The more fall and flow that you have, the more potential power you can generate. You can measure flow by building a weir in the creek and measuring how fast it will fill up a 5 gallon bucket.
- Your pipeline must be of a big enough diameter to minimize friction loss in the pipe. Your micro-hydro supplier can give you specific information regarding this.
- Nozzle size and turbine wheel type are all interrelated to your total head and flow. Again, your hydro supplier will customize these for your specific application. Often, different size nozzles are designed to be switched in and out as stream conditions change throughout the year.
- There are two main types of turbines, impulse and reaction. With impulse turbines, a jet of water is created by the nozzle and squirted onto the wheel. Reaction turbines are more akin to propellor that spins **INSIDE** the pipe, generating power.
- The 3 primary impulse turbine wheel types are Pelton, Turgo, and Cross-flow. Pelton wheels are used in low flow, high head conditions, and Cross-flow wheels are for high flow, low head installations. Turgo wheels are somewhere in the middle. Francis and propellor turbines are the most common reaction type; the Francis design is very similar to the innards of a centrifugal pump.
- Home built reaction turbines have been built using centrifugal pumps running in reverse (generating power with moving water instead of using power to move the water). We hope to have more information about experimenting with this soon.

[HOME](#)
[PRODUCTS](#)
[DISCUSSION BOARD](#)
[DAILY NEWS](#)
[CONSERVATION](#)
[BATTERIES](#)
[SUN](#)
[WIND](#)
[HYDRO](#)
[FOSSIL FUELS](#)
[EXPERIMENTS](#)
[ORDER NOW!](#)

[WATER PUMPING](#)

[POWER SYSTEMS](#)

[EFFICIENT LIGHTING](#)

[LINKS](#)

---

<mailto:info@otherpower.com>

©2000 by [FORCEFIELD](#)

---

[WWW.WONDERMAGNET.COM](http://WWW.WONDERMAGNET.COM)